PROTEKTOR



CONSTRUCT Offshore

Offshore safety shoe equipped with a waterproof and vapor-permeable cloth. The shoes have a heat-resistant PU / Rubber sole with a self-cleaning outsole. Reflective elements increase work safety in darkened rooms.

³³ ♀ ∞ ∅ ♀ ♀ ∅ ↓ ∞ & ⇔ ⇔ ∯ ♀ ∞ ज ∞ ∞ ♀ ♀ ♀ ∞ ↓ ∞ ○ ♀ × ≥ ▲ © ₽⊺

Construction / Finishing works, Firefighter and medical rescue, Heavy industry Ankle boots
Ankle boots
Black
EN ISO 20345:2011
IPS-1439-7/2022 edition 1
increased breathability, increased durability of the upper, composite toe cap, metal free, easy-clean upper, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, reflective elements, bellows tongue, disinfection, PRO-TENDON technology (Achilles tendon protection)
increased water resistance
lining - waterproof, vapor-permeable membrane
increased upper strength
grain leather - excellent tensile strength parameters, the required minimum is 15 N/mm2 and our result is 29.1 N/mm2
outsole - increased abrasion resistance required result in the standard: less than or equal to 150 mm3 - our result 70 mm3, energy absorption in the heel area according to the standard minimum 20J, our result 30.6J
resistance of the outsole to acids
heat-resistant outsole (resistant to contact with 300°C for 60 seconds)
outsole - protection against ankle sprains, thanks to the increased stability provided by the extended heel area - up to 92 mm wide in size 42
outsole design for easy removal using the "shoe against shoe" method
Grain leather
Technological fabric, membrane lining
Fabric, replaceable insole
Pu/Rubber, heat-resistant sole, sole tread allowing climbing the ladder safely, resistance to acids, PRT FLEX technology, SHOCK ABSORBER technology, ANA-TECH technology (extended heel surface in the sole), SELF CLEAN technology (self-cleaning sole)
Shoelaces
H 1/2
FR 35-50 CM 22,5-32,5 UK 3-14,5
-

Weight (half pair) +/- 3% t.