



**SOLIGOR**  
01-010968



Brand	PROTEKTOR
Industry	Heavy industry, Light industry
Product type	Ankle boots
Color	● Black
Norm	EN ISO 20345:2011
Certificate	80/2022/PPE/1439/B wyd.2
Product features	increased breathability, steel toe cap, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, bellows tongue, disinfection, PRO-TENDON technology (Achilles tendon protection)
Product characteristics	<p>increased breathability</p> <p>lining - increased water vapor permeability in the requirements of min. 0.8 mg / (cm<sup>2</sup> * h) - our result is 42.9 mg / (cm<sup>2</sup> * h), water vapor coefficient is required at least 15 mg / cm<sup>2</sup> and our result is 343.3 mg/cm<sup>2</sup></p> <p>collar and tongue material - increased water vapor permeability in the requirements of at least 0.8 mg / (cm<sup>2</sup> * h) - our result is 58.2 mg / (cm<sup>2</sup> * h), water vapor coefficient is required at least 15 mg / cm<sup>2</sup> and our result is 466 mg/cm<sup>2</sup></p> <p>acid and basic resistance</p> <p>resistance to short-term contact with a hot substrate at a temperature of 180°C</p> <p>footwear meets the requirements for the operation of underground mining plants</p>
Upper material	Grain leather/Fabric
Lining & Sock	Technological fabric
Insole	Fabric, antibacterial insole, replaceable insole
Sole	Pu/Pu, sole tread allowing climbing the ladder safely, resistance to acids, resistance to bases, resistance to short-term contact with hot ground at 180 ° C, PRT FLEX technology, SHOCK ABSORBER technology, SELF CLEAN technology (self-cleaning sole)
Fastener type	Shoelaces, quick donning system, quick shoe removal system
Available sizes	FR 36-48 CM 23-31 UK 3,5-13
Weight (half pair s.42) +/- 3% t.	0,85 kg