

BASIC

01-252375



Brand	PROTEKTOR
Industry	Light industry, Transport / Warehouses
Product type	Shoes
Color	● Black
Norm	EN ISO 20345:2011
Certificate	159/2023/PPE/1439/B wyd.1
Product features	increased breathability, composite toe cap, metal free, easy-clean upper, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, bellows tongue
Product characteristics	increased breathability velour microfibre - water vapour coefficient in the requirements of the standard minimum 15 mg/cm², our result 31.4 mg/cm² outsole - increased abrasion resistance required by the standard: less than or equal to 150 mm³ - our result 53 mm³ energy absorption in the heel area according to the standard: minimum 20J, our result 30J resistance of the outsole to acids and alkalis resistance of the outsole to short-term contact with hot surfaces at a temperature of 180°C the outsole complies with the SR slip resistance test according to the new standard EN ISO 20345:2022
Upper material	Microfiber/Fabric
Lining & Sock	Fabric
Insole	Fabric, replaceable insole
Sole	Pu/Pu, resistance to acids, resistance to bases, resistance to short-term contact with hot ground at 180 ° C, PRT FLEX technology, SHOCK ABSORBER technology
Fastener type	Shoelaces
Fit type	H
Available sizes	FR 36-47 CM 23-30,5 UK 3,5-12
Weight (half pair s.42) +/- 3% t.	0,49 kg