

## ACTIVE

02-0085080



Active slippers is a line of specialized products recommended for professionals whose work and daily duties require constant movement, as well as standing for many hours. Their light weight helps to reduce leg fatigue. The shock absorber technology absorbs vibrations and unevenness, protects against injuries and ensures high comfort - even during many hours of work. Excellent performance parameters make Active line ideal for hospitals, nursing homes and the food industry.



|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brand                             | ABEBA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Industry                          | Gastronomy / Kitchen, Horeca, Hospitals, Pharmaceuticals                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Product type                      | Clog                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Color                             | ○ White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Norm                              | EN ISO 20347:2012                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Certificate                       | 19/2022/PPE/1439/B edition 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product features                  | increased breathability, increased durability of the upper, easy-clean upper                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product characteristics           | <p>increased durability of the upper</p> <p>leather - tear resistance in requirements not less than 120 N, our result 206 N, tensile strength in requirements not less than 15 N / mm<sup>2</sup>, our result 25 N / mm<sup>2</sup></p> <p>increased breathability</p> <p>lining - increased water vapor permeability in the requirements of minimum 2.0 mg / (cm<sup>2</sup> * h) - our result is 14.6 mg / (cm<sup>2</sup> * h), the water vapor coefficient is required at least 20 mg / cm<sup>2</sup> and our result is 117.2 mg / cm<sup>2</sup></p> <p>sole resistance to acids and bases</p> <p>sole resistance to short-term contact with hot ground at 180 ° C</p> |
| Upper material                    | Grain leather                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Lining & Sock                     | Fabric                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Insole                            | Fabric, integrated insole                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Sole                              | Pu/Pu, resistance to acids, resistance to bases, resistance to short-term contact with hot ground at 180 ° C, PRT FLEX technology, SHOCK ABSORBER technology, SELF CLEAN technology (self-cleaning sole)                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Fastener type                     | Buckle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Fit type                          | G 1/2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Available sizes                   | FR 36-49 CM 23-32 UK 3,5-14                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Weight (half pair s.42) +/- 3% t. | 0,36 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |