



## BASIC

01-252373



|                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brand                             | PROTEKTOR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Industry                          | Light industry, Transport / Warehouses                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Product type                      | Ankle boots                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Color                             | ● Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Norm                              | EN ISO 20345:2011                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Certificate                       | 159/2023/PPE/1439/B wyd.1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Product features                  | increased breathability, composite toe cap, metal free, easy-clean upper, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, bellows tongue                                                                                                                                                                                                                                                                                                                                                                                        |
| Product characteristics           | <p>increased breathability</p> <p>velour microfiber - in the requirements of the standard water vapor coefficient minimum 15 mg/cm<sup>2</sup>, our result 31.4 mg/cm<sup>2</sup></p> <p>increased abrasion resistance required by the standard: less than or equal to 150 mm<sup>3</sup> - our result 53 mm<sup>3</sup></p> <p>energy absorption in the heel area according to the standard minimum 20J, our result 30J</p> <p>resistance of the sole to acids and alkalis</p> <p>resistance of the sole to short-term contact with hot ground at a temperature of 180°C</p> |
| Upper material                    | Microfiber/Fabric                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Lining & Sock                     | Fabric                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Insole                            | Fabric, replaceable insole                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Sole                              | Pu/Pu, resistance to acids, resistance to bases, resistance to short-term contact with hot ground at 180 ° C, PRT FLEX technology, SHOCK ABSORBER technology                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Fastener type                     | Shoelaces                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Fit type                          | H                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Available sizes                   | FR 36-47 CM 23-30,5 UK 3,5-12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Weight (half pair s.42) +/- 3% t. | 0,58 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |